## **INOX | Upright Cabinets**

BAKERY REFRIGERATED CABINETS ► STATIC ► CHILLER



#### **GENERAL FEATURES**

EURONORM refrigerated upright cabinet	•
White coated steel for external side and stainless steel for inner side	•
Static cooling system with fan assisted cooling	•
Condenser with anti-corrosion treatment	•
Bottom side engine room (for comfortable storage in the cabinet)	•
Automatic compressor cycle defrost	•
Digital thermostat with "opening door" and "Hi temperature" alarm	•
Foaming Agent Cyclopentane (80mm)	•
Removable Gasket	•
LED light and lock fitted as standard	•
Door: Self closing and reversible door fitted as standard	•
Set of 10 slides for bakery tray 600X400	•
Plastic thermal-braker anti-condensation as chamber body frame	•
N.4 Adjustable feet - S/S feet or castor with brake (Option)	•
Energy efficiency class: D	•

#### **TECHNICAL SPECIFICATIONS**

External Dimensions (WxDxH mm)	740x880x2025
Internal Dimensions (WxDxH mm)	580x710x1430
Noise level	48 dB(A)
Consumption	2.5 kWh/24h
Capacity	600 L
Rated Power	350 W
Net Weight	150 Kg
Temperature	+2° ~ +8°C
Gross Weight	161 Kg
Packaging dimensions (WxDxH mm)	760x900x2150
Loading quantities 20'/40'/40'HQ	18/39/39

#### **CERTIFICATION**

(E C



RoHS

# BY 740S







































Digital thermostat and door lock fitted handle as standard



Foamed door



Easily acces for clean condenser filter



Inner vertical LED



Euronorm 600x400mm set of guides (10 Layer for each door)



Bottom hole for easily clean and dry the item

### **PRODUCT DIMENSIONS**







