# **ABS | Upright Cabinets**

FREEZER UPRIGHT ▶ CLASS A ▶ INOX ▶ WITH BASKETS



#### **GENERAL FEATURES**

| 600 Lt. Freezer upright (CLASS A)   | • |
|---|---|
| S/S external cabinet, thermoformed internally                                   | • |
| Static cooling: fixed evaporator shelves (N.6 Layers) with fan assisted cooling | • |
| Manual Defrost  | • |
| Foaming Agent Cyclopentane (65mm per side)                                      | • |
| Digital Thermostat  | • |
| Opening door alarm/High temperature alarm                                       | • |
| Removable Gasket  | • |
| Door: Self closing and reversible door fitted as standard                       | • |
| Lock and main switch fitted as standard   | • |
| N.13 Basket included  | • |
| N.2 Adjustable feet + N.2 Rollers at the back                                   | • |
| Energy efficiency class: A  | • |

### **TECHNICAL SPECIFICATIONS**

| Capacity                         | 600 L         |
|----------------------------------|---------------|
| Temperature                      | -23°C ~ -18°C |
| Consumption                      | 2.277 kWh/24h |
| Rated Power                      | 215 W         |
| Noise level                      | 68 dB(A)      |
| Net Weight                       | 99 Kg         |
| Gross Weight                     | 112 Kg        |
| External Dimensions (WxDxH mm)   | 775x729x1900  |
| Internal Dimensions (WxDxH mm)   | 625x528x1647  |
| Packaging dimensions (WxDxH mm)  | 835x792x2070  |
| Loading quantities 20'/40'/40'HQ | 20/42/42      |

### **CERTIFICATION**

(E C



RoHS

# CNX 613



























Pressure valve for easily opening door



N.12 Basket (Dim: 440x290x200



N.1 Bottom basket 600x220x200 mm)



## **PRODUCT DIMENSIONS**







