

INOX | Upright Cabinets

REFRIGERATED CABINETS ▶ GN2/1-NO FROST ▶ CHILLER

CR 7



GENERAL FEATURES

- GN2/1 Refrigerated upright cabinet (CLASS A)
- Stainless Steel exterior and interior
- Plastic thermal-braker anti-condensation as chamber body frame
- Inner with embossed rear shelf stopper and wave for easy cleaning
- Ventilated Cooling
- Evaporator with anti-corrosion treatment
- Automatic defrost with electric heater
- Foaming Agent Cyclopentane (85mm)
- Digital thermostat with "opening door" and "High temperature" alarm
- Removable Gasket
- LED light and lock fitted as standard
- Door: Self closing and reversible door fitted as standard
- Adjustable shelves GN2/1: 3 + 1
- N.4 S/S Adjustable feet - (Lockable castor as Optional)
- Inverter compressor
- Energy efficiency class: A

TECHNICAL SPECIFICATIONS

Capacity	550 L
Temperature	-2°C ~ +8°C
Consumption	0.88 kWh/24h
Rated Power	200 W
Noise level	59 dB(A)
Net Weight	146 Kg
Gross Weight	161 Kg
External Dimensions (WxDxH mm)	705x912x2085
Internal Dimensions (WxDxH mm)	535x665x1390
Packaging dimensions (WxDxH mm)	725x930x2170
Loading quantities 20'/40'/40'HQ	18/39/39

CERTIFICATION


CE RoHS



ENERGY SAVING



TROPICALIZED UPRIGHT



GAS

R600a

[[]]

85 mm


A


ENERGY CLASS

5


CLIMATIC CLASS


40°C







LED









DETAILS




The items can be supplied either with adjustable feet or lockable castor




Top horizontal LED light




Embossed rear shelf stopper




Inner stainless steel waved guides




Inverter compressor




"Door opening and High temperature alarm" as standard



Bottom hole for easily clean and dry the item



Evaporator with anti-corrosion treatment



Digital Thermostat

PRODUCT DIMENSIONS

