INOX | Saladette

SALADETTE ► GN1/1 ► OPEN TOP





















DETAILS







Curved edge for easy cleaning



Engine room lock fitted as standard



Anti-condensation themal-braker on door frame



Inner embossed door design for a better sealing



to pull out for manageble after sales servicing



Inner assistance fan



Door design

GENERAL FEATURES

| GN1/1 Refrigerated saladette (OPEN TOP) | • |
|--------------------------------------------------------------------|---|
| Stainless Steel exterior and interior | • |
| Static Cooling | • |
| Automatic compressor cycle defrost | • |
| Foaming Agent Cyclopentane (45mm per side) | • |
| Digital Thermostat | • |
| Sliding engine room for a manageble after sales servicing | • |
| Plastic thermal-braker as chamber body frame | • |
| Easy removable condenser filter | • |
| Separated plastic water tray | • |
| Front panel tilted holes for better air circulation | • |
| Adjustable shelves GN1/1: 3 pcs | • |
| Self closing door (New inner embossed design for a better sealing) | • |
| Removable Gasket | • |
| Engine room lock fitted as standard | • |
| N.2 Adjustable feet in the front + N.4 fix rollers | • |
| Holder spacer for GN pans (included) | • |
| Energy efficiency class: - | • |

• :· 20 :

TECHNICAL SPECIFICATIONS

| Capacity | 350L |
|----------------------------------|---------------|
| Temperature | +0° ~ +8°C |
| Consumption | 4.34 kWh/24h |
| Rated Power | 233 W |
| Noise level | 48 dB(A) |
| Net Weight | 91 Kg |
| Gross Weight | 115 Kg |
| External Dimensions (WxDxH mm) | 1365x700x890 |
| Internal Dimensions (WxDxH mm) | 1275x586x502 |
| Packaging dimensions (WxDxH mm) | 1420x750x1030 |
| Loading quantities 20'/40'/40'HQ | 24/48/48 |

CERTIFICATION

< **€ €**



RoHS

PRODUCT DIMENSIONS







