

ABS | Upright Cabinets

REFRIGERATED UPRIGHT ▶ GLASS DOOR ▶ WHITE PAINTED

CRG 2

GAS R600a		 50 mm	A ENERGY CLASS	3 CLIMATIC CLASS	 30°C
 LED					

DETAILS

 Inner assistance fan	 Air circulating fan assistance	 Blue backlit main switch
 Shelf with small distance between the line and bottom shelf fitted as standard	 External cylindrical handle in stainless steel (Steel color for X Version)	



GENERAL FEATURES

- 200 Lt. Refrigerated upright (GLASS DOOR)
- White external cabinet, thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (50mm per side)
- Digital Thermostat and internal LED light
- High temperature alarm
- Removable Gasket
- Reversible door
- Lock and main switch fitted as standard
- Adjustable shelves: 2 Pcs + 1 Pcs Bottom
- N.2 Adjustable feet + N.2 Rollers at the back
- Stainless steel external handle
- Energy efficiency class: A

TECHNICAL SPECIFICATIONS

Capacity	200 L
Temperature	+2°C ~ +8°C
Consumption	1.036 kWh/24h
Rated Power	60 W
Noise level	40 dB(A)
Net Weight	45.5 Kg
Gross Weight	50 Kg
External Dimensions (WxDxH mm)	598x679x838
Internal Dimensions (WxDxH mm)	477x443x652
Packaging dimensions (WxDxH mm)	650x680x880
Loading quantities 20'/40'/40'HQ	48/108/162

CERTIFICATION

CE RoHS

PRODUCT DIMENSIONS

