

# ABS | Upright Cabinets

REFRIGERATED UPRIGHT ▶ GLASS DOOR ▶ INOX

CRXG 2

GAS <b>R600a</b>		 50 mm	<b>A</b> ENERGY CLASS	<b>3</b> CLIMATIC CLASS	 30°C
 LED					

## DETAILS

 Inner assistance fan	 Air circulating fan assistance	 Blue backlit main switch
 Shelf with small distance between the line and bottom shelf fitted as standard	 External cylindrical handle in stainless steel (Steel color for X Version)	



## GENERAL FEATURES

- 200 Lt. Refrigerated upright (GLASS DOOR)
- S/S external cabinet, thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (50mm per side)
- Digital Thermostat and internal LED light
- High temperature alarm
- Removable Gasket
- Reversible door
- Lock and main switch fitted as standard
- Adjustable shelves: 2 Pcs + 1 Pcs Bottom
- N.2 Adjustable feet + N.2 Rollers at the back
- Stainless steel external handle
- Energy efficiency class: A

## TECHNICAL SPECIFICATIONS

Capacity	<b>200 L</b>
Temperature	<b>+2°C ~ +8°C</b>
Consumption	<b>1.036 kWh/24h</b>
Rated Power	<b>60 W</b>
Noise level	<b>40 dB(A)</b>
Net Weight	<b>46.2 Kg</b>
Gross Weight	<b>50.5 Kg</b>
External Dimensions (WxDxH mm)	<b>598x679x838</b>
Internal Dimensions (WxDxH mm)	<b>477x443x652</b>
Packaging dimensions (WxDxH mm)	<b>650x680x880</b>
Loading quantities 20'/40'/40'HQ	<b>48/108/162</b>

## CERTIFICATION

CE RoHS

## PRODUCT DIMENSIONS

