INOX | Dual temperature drawers

DUAL TEMPERATURE ► GN1/1 ► REFRIGERATED DRAWERS















DETAILS







Backlit main switch and digital thermostat fitted as standard



Sliding engine easy to pull out for manageble after sales servicing



Easily acces for clean condenser filter



Evaporator with anti-corrosion treatment



Removable Gasket

GENERAL FEATURES

| Double drawers switchable cooling/freezer (N.6 GN1/1 Pans) | • |
|---|---|
| Dual temperature model (Easily switchable between cooler and freezer) | • |
| Stainless Steel exterior and interior | • |
| Ventilated Cooling | • |
| Automatic defrost with electric heater | • |
| Evaporator with anti-corrosion treatment | • |
| Foaming Agent Cyclopentane (50mm per side) | • |
| Digital Thermostat | • |
| White backlit main switch | • |
| Sliding engine room for a manageble after sales servicing | • |
| Easy removable condenser filter | • |
| Front panel tilted holes for better air circulation | • |
| Sliding drawers GN1/1 suitable for pans 150mm depth | • |
| Removable Gasket | • |
| N.4 Castor (N.2 in the front with brake) | • |
| Energy efficiency class: - | • |
| | |

PRODUCT DIMENSIONS

40 870 740 क 1230

TECHNICAL SPECIFICATIONS

| Capacity | 265 L |
|----------------------------------|---------------------|
| Temperature | -2°~+8°C/-21°~-18°C |
| Consumption | 5.2/13.6 kWh/24h |
| Rated Power | 689 W |
| Noise level | 42 dB(A) |
| Net Weight | 150 Kg |
| Gross Weight | 165 Kg |
| External Dimensions (WxDxH mm) | 1230x700x870 |
| Internal Dimensions (WxDxH mm) | 951x520x150 |
| Packaging dimensions (WxDxH mm) | 1300x750x945 |
| Loading quantities 20'/40'/40'HQ | 26/54/54 |

CERTIFICATION

(E C



RoHS





