INOX | Upright Cabinets

REFRIGERATED CABINETS ► GN2/1-VENTILATED ► FREEZER



GENERAL FEATURES

| GN2/1 Freezer upright cabinet | • |
|---|---|
| Stainless Steel exterior and interior | • |
| Ventilated Cooling | • |
| Evaporator and condenser with anti-corrosion treatment | • |
| Bottom side engine room (for comfortable storage in the cabinet) | • |
| Hot gas defrost system | • |
| Digital thermostat with "opening door" and "Hi temperature" alarm | • |
| Foaming Agent Cyclopentane (80mm) | • |
| Removable Gasket | • |
| LED light and lock fitted as standard | • |
| Door: Self closing and reversible door fitted as standard | • |
| Adjustable shelves GN2/1: 5 Pcs | • |
| Plastic thermal-braker as chamber body frame (Hot pipe system) | • |
| Pressure valve for easily opening door | • |
| N.4 Adjustable feet - S/S feet or castor with brake (Option) | • |
| Energy efficiency class: D | • |

TECHNICAL SPECIFICATIONS

| External Dimensions (WxDxH mm) | 740x880x2025 |
|----------------------------------|--------------|
| Internal Dimensions (WxDxH mm) | 580x710x1430 |
| Noise level | 48 dB(A) |
| Consumption | 6.1 kWh/24h |
| Capacity | 600 L |
| Rated Power | 420 W |
| Net Weight | 144 Kg |
| Temperature | -18° ~ -22°C |
| Gross Weight | 155 Kg |
| Packaging dimensions (WxDxH mm) | 760x900x2150 |
| Loading quantities 20'/40'/40'HQ | 18/39/39 |

CERTIFICATION

(E C



RoHS

QNX 688V

























Stainless steel feet

Digital thermostat as standard

Foamed door







clean condenser filter

Inner vertical LED

Multi functional set of guide ("E" form)



Cabinet suitable for GN2/1 pans



Evaporator with anti-corrosion treatment

PRODUCT DIMENSIONS







