

ABS | Upright Cabinets

REFRIGERATED UPRIGHT ▶ WHITE PAINTED



GENERAL FEATURES

- 400 Lt. Refrigerated upright
- White external cabinet, thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (60mm per side)
- Digital Thermostat
- Removable Gasket
- Reversible door
- Handle along door profile
- Doors lock fitted as standard
- Adjustable shelves: 4 Pcs + 1 BOTTOM Shelf
- N.2 Adjustable feet + N.2 Rollers at the back
- Energy efficiency class: D

TECHNICAL SPECIFICATIONS

Capacity	400 L
Temperature	+2°C ~ +10°C
Consumption	1.71 kWh/24h
Rated Power	200 W
Noise level	57 dB(A)
Net Weight	62 Kg
Gross Weight	71 Kg
External Dimensions (WxDxH mm)	600x685x1890
Internal Dimensions (WxDxH mm)	480x540x1680
Packaging dimensions (WxDxH mm)	650x705x2030
Loading quantities 20'/40'/40'HQ	27/54/54

CERTIFICATION

CE RoHS



QR 400

GAS

R600a

60 mm

4

CLIMATIC CLASS

38°C

DETAILS

Digital Thermostat

Lock fitted as standard

PRODUCT DIMENSIONS

