

INOX | Upright Cabinets

REFRIGERATED CABINETS ▶ GN2/1-NO FROST ▶ CHILLER

QR 6-5A



GENERAL FEATURES

- GN2/1 Refrigerated upright cabinet (CLASS A)
- Stainless Steel exterior and interior
- Plastic thermal-braker anti-condensation as chamber body frame
- Ventilated Cooling
- Inverter compressor
- Evaporator with anti-corrosion treatment
- Automatic defrost with electric heater
- Foaming Agent Cyclopentane (80mm)
- Curved edge for easy cleaning
- Digital Thermostat
- White backlit main switch
- LED light and lock fitted as standard
- Removable Gasket
- Door: Self closing and reversible door fitted as standard
- Foamed door handle
- Adjustable shelves GN2/1: 3 + 1
- N.4 S/S Adjustable feet - (Lockable castor as Optional)
- Energy efficiency class: A

TECHNICAL SPECIFICATIONS

| | |
|----------------------------------|---------------|
| Capacity | 546 L |
| Temperature | -2° ~ +8°C |
| Consumption | 0.723 kWh/24h |
| Rated Power | 73 W |
| Noise level | 58 dB(A) |
| Net Weight | 109.00 Kg |
| Gross Weight | 122.00 Kg |
| External Dimensions (WxDxH mm) | 700x850x2045 |
| Internal Dimensions (WxDxH mm) | 534x685x1485 |
| Packaging dimensions (WxDxH mm) | 720x870x2110 |
| Loading quantities 20'/40'/40'HQ | 20/42/42 |

CERTIFICATION


CE RoHS



ENERGY SAVING



TROPICALIZED UPRIGHT



GAS
R600a


[[
80 mm


A
ENERGY CLASS


5
CLIMATIC CLASS

40°C

LED







DETAILS



The items can be supplied either with adjustable feet or lockable castor



Inverter compressor



Evaporator with anti-corrosion treatment



Inner stainless steel waved guides



Anti-condensation "thermal-braker" on door frame



Lock fitted as standard



Digital control and white backlit main switch



Inner LED light



Cabinet suitable for GN2/1 pans

PRODUCT DIMENSIONS

