

INOX | Upright Cabinets

REFRIGERATED CABINETS ▶ GN2/1-VENTILATED ▶ CHILLER

QRX 688V



DETAILS



GENERAL FEATURES

- GN2/1 Refrigerated upright cabinet
- Stainless Steel exterior and interior
- Ventilated Cooling
- Evaporator and condenser with anti-corrosion treatment
- Bottom side engine room (for comfortable storage in the cabinet)
- Hot gas defrost system
- Digital thermostat with "opening door" and "Hi temperature" alarm
- Foaming Agent Cyclopentane (80mm)
- Removable Gasket
- LED light and lock fitted as standard
- Door: Self closing and reversible door fitted as standard
- Adjustable shelves GN2/1: 5 Pcs
- Plastic thermal-braker anti-condensation as chamber body frame
- N.4 Adjustable feet - S/S feet or castor with brake (Option)
- Energy efficiency class: C

TECHNICAL SPECIFICATIONS

External Dimensions (WxDxH mm)	740x880x2025
Internal Dimensions (WxDxH mm)	580x710x1430
Noise level	48 dB(A)
Consumption	1.55 kWh/24h
Capacity	600 L
Rated Power	310 W
Net Weight	144 Kg
Temperature	-2° ~ +8°C
Gross Weight	155 Kg
Packaging dimensions (WxDxH mm)	760x900x2150
Loading quantities 20'/40'/40'HQ	18/39/39

CERTIFICATION



PRODUCT DIMENSIONS

