

ABS | Upright Cabinets

REFRIGERATED UPRIGHT ▶ GLASS DOOR ▶ INOX

QRXG 200



60 mm	H2	-1°C +10°C	A ENERGY CLASS	3 +25°C/60RH
Key icon	LED	Lightbulb icon	GAS R600a	Fan icon

DETAILS

<p>Linked Image Not Found</p> <p>Digital Thermostat</p>	<p>Linked Image Not Found</p> <p>Top horizontal LED light</p>	<p>Shelf with small distance between the line and bottom shelf fits as standard</p>
<p>Linked Image Not Found</p> <p>External cylindrical handle in stainless steel</p>	<p>Linked Image Not Found</p> <p>Lock fitted as standard</p>	<p>Linked Image Not Found</p> <p>The items can be supplied either with adjustable feet or lockable castor</p>

GENERAL FEATURES

- 200 Lt. Refrigerated upright (GLASS DOOR)
- S/S external cabinet, thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (60mm per side)
- Digital Thermostat
- Inner LED light
- Removable Gasket
- Doors lock fitted as standard
- Stainless steel external handle
- Adjustable shelves: 2 Pcs + 1 Pcs Bottom
- N.2 Adjustable feet + N.2 Rollers at the back
- HIGH S/S Adjustable feet or Lockable castor as optional
- Energy efficiency class: A

TECHNICAL SPECIFICATIONS

Capacity	200 L
Temperature	M2 (-1°C-+7°C)
Consumption	1.05 kWh/24h
Rated Power	100 W
Noise level	68 dB(A)
Net Weight	38 Kg
Gross Weight	42 Kg
External Dimensions (WxDxH mm)	600x678x835
Internal Dimensions (WxDxH mm)	500x410x660
Packaging dimensions (WxDxH mm)	640x675x880
Loading quantities 20'/40'/40'HQ	54/108/162

CERTIFICATION

CE RoHS

PRODUCT DIMENSIONS

