

ABS | Upright Cabinets

REFRIGERATED UPRIGHT ▶ GLASS DOOR ▶ INOX



GENERAL FEATURES

- 400 Lt. Refrigerated upright (GLASS DOOR)
- Gray external cabinet, thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (60mm per side)
- Digital Thermostat
- Removable Gasket
- Reversible door
- Double tempered glass with Low-e (Low emissivity glasses) and Argon gas
- Inner horizontal LED light
- Door with vertical cylindrical handle
- Doors lock fitted as standard
- Adjustable shelves: 4 Pcs + 1 BOTTOM Shelf
- N.2 Adjustable feet + N.2 Rollers at the back
- Energy efficiency class: A

TECHNICAL SPECIFICATIONS

Capacity	400 L
Temperature	M1 (-1°C~+5°C)
Consumption	1.96 kWh/24h
Rated Power	200 W
Noise level	58 dB(A)
Net Weight	77 Kg
Gross Weight	86 Kg
External Dimensions (WxDxH mm)	600x723x1890
Internal Dimensions (WxDxH mm)	480x540x1680
Packaging dimensions (WxDxH mm)	650x705x2042
Loading quantities 20'/40'/40'HQ	27/54/54

CERTIFICATION

CE RoHS

QRXG 400

M1

-1°C
+5°C

A

ENERGY CLASS

3

+25°C/60RH

38°C

GAS

R600a

60 mm

LED

DETAILS

Digital Thermostat

Lock fitted as standard

Top horizontal LED light

Handle along door profile

PRODUCT DIMENSIONS

