

ABS | Upright Cabinets

REFRIGERATED UPRIGHT ► GLASS DOOR ► INOX



GENERAL FEATURES

- 600 Lt. Refrigerated upright (GLASS DOOR)
- Gray external cabinet, thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (60mm per side)
- Digital Thermostat
- Removable Gasket
- Reversible door
- Double tempered glass with Low-e (Low emissivity glasses) and Argon gas
- Inner horizontal LED light
- Door with vertical cylindrical handle
- Doors lock fitted as standard
- Adjustable shelves: 4 Pcs + 1 BOTTOM Shelf
- N.2 Adjustable feet + N.2 Rollers at the back
- Energy efficiency class: B

TECHNICAL SPECIFICATIONS

Capacity	600 L
Temperature	M1 (-1°C~+5°C)
Consumption	2.69 kWh/24h
Rated Power	200 W
Noise level	58 dB(A)
Net Weight	104 Kg
Gross Weight	116 Kg
External Dimensions (WxDxH mm)	780x768x1890
Internal Dimensions (WxDxH mm)	660x585x1680
Packaging dimensions (WxDxH mm)	830x750x2042
Loading quantities 20'/40'/40'HQ	21/42/42

CERTIFICATION

CE RoHS

QRXG 600

M1
-1°C
+5°C

B
ENERGY CLASS

3
+25°C/60RH

36°C

GAS
R600a

60 mm

LED

DETAILS

Cabinet suitable for GN2/1 pans

Cabinet suitable for N.2 GN1/1 pans

Digital Thermostat

Lock fitted as standard

Top horizontal LED light

Handle along door profile

PRODUCT DIMENSIONS

