

# INOX | Blast Chillers

BLAST CHILLER

# RF 70A



The items can be supplied either with adjustable feet or lockable castor

ECM Fan (For Low energy consumption/Low noise level)

GAS  
**R290**

75 mm

**5**  
CLIMATIC CLASS

40°C

## DETAILS



The items can be supplied either with adjustable feet or lockable castor



Inner view of the unit



Needle probe



Digital control



Suitable for tray EURONORM 600x400mm or GASTRONORM GN1/1



Anti-condensation "thermal-braker" on door frame



Evaporator with anti-corrosion treatment



"FROST BUST" (-40°C Cycle) and "ICE CREAM" settings



Ice Cream shelves set as optional (Pans NOT included)

## GENERAL FEATURES

- GNI/1 and EURONORM 600x400mm Upright Blast chiller
- Stainless Steel exterior and interior
- Ventilated Cooling with Manual defrost
- Plastic thermal-braker as chamber body frame (Heated wire)
- Evaporator with anti-corrosion treatment
- Foaming Agent Cyclopentane (75mm per side - CFC Free)
- Digital Thermostat with Buzzer alarm
- Error message directly in the display
- Chilling chamber in stainless steel
- Door microswitch for stop inner fan with open door
- Prepared for condensation water tray (Not included)
- Reversible door / Needle probe fitted as standard
- Tray configuration: 70mm distance between trays
- N.4 S/S Adjustable feet - (Lockable castor as Optional)
- Temperature controlled or temporized blast cycles (Soft/Hard)
- Automatic storage mode at the end of blast chilling cycle
- ECM Fan (For Low energy consumption/Low noise level)
- Separate button for "ICE CREAM" Cycle
- Separate button for "-40°C" Cycle
- ICE CREAM kit (PANS not included) optional

## TECHNICAL SPECIFICATIONS

Capacity	<b>Ch.23Kg/Fr.18Kg</b>
Temperature	<b>+10°C ~ -40°C</b>
Consumption	<b>N/A kWh/24h</b>
Rated Power	<b>1180W</b>
Noise level	<b>60 dB(A)</b>
Net Weight	<b>116 Kg</b>
Gross Weight	<b>138 Kg</b>
External Dimensions (WxDxH mm)	<b>790x900x1377</b>
Internal Dimensions (WxDxH mm)	<b>640x452x730</b>
Packaging dimensions (WxDxH mm)	<b>840x910x1500</b>
Loading quantities 20'/40'/40'HQ	<b>12/28/28</b>

## CERTIFICATION

CE RoHS

## PRODUCT DIMENSIONS

