

INOX | Upright Cabinets

REFRIGERATED CABINETS ▶ HARDERING ▶ FREEZER

SHF 700



GENERAL FEATURES

- Ice cream hardening uprights
- Stainless Steel exterior and interior
- Plastic thermal-braker as chamber body frame (Heated)
- Ventilated Cooling + Inner variable speed fan
- Evaporator with anti-corrosion treatment
- Hot gas defrost system
- Foaming Agent Cyclopentane (80mm)
- Digital Thermostat
- LED light and lock fitted as standard
- Removable Gasket
- Door with self closing door
- Opening door alarm
- Fast temperature recovery system (check the tab)
- Adjustable shelves: 3 Pcs
- Items equipped with "C" shape guide (with GN 2/1 Pans compatibility)
- Suitable to store ice cream pans (GN1/3 and 5 Lt.) and ice cream tubes (2.5 and 3 Gallons)
- N.4 swivel castor with brakes integrated fitted as standard
- Energy efficiency class: -

TECHNICAL SPECIFICATIONS

Capacity	650 L
Temperature	-32 F - -13 F
Consumption	0 kWh/24h
Rated Power	1000 W
Noise level	0 dB(A)
Net Weight	189.50 Kg
Gross Weight	205.00 Kg
External Dimensions (WxDxH mm)	790x930x2065
Internal Dimensions (WxDxH mm)	642x755x1548
Packaging dimensions (WxDxH mm)	835x982x2100
Loading quantities 20'/40'/40'HQ	14/28/28

CERTIFICATION

CE RoHS

42 GN1/3 STANDARD 14.17x6.49x4.72 cm	36 GN1/3 5 Lt. Gelato 14.17x9.84x3.14 cm
254 mm 3 GALLONS 12 WITH RACKS 16 WITHOUT RACKS Ø305 mm	254 mm 2.5 GALLONS 16 WITH RACKS 24 WITHOUT RACKS Ø254 mm

		GAS R290	80 mm	4 CLIMATIC CLASS	36°C

DETAILS

Digital Thermostat	Anti-tilted castors fitted as standard	All shelves mounted with anti-tipping system
Anti-condensation "thermal-braker" on door frame	Lock fitted as standard	Evaporator with anti-corrosion treatment
		External cylindric handle in stainless steel

PRODUCT DIMENSIONS

