

# DRINKS | Backbars

BACK BARS ► HINGED SOLID DOORS

# QB 400



|  |                    |           |                          |                            |          |
|--|--------------------|-----------|--------------------------|----------------------------|----------|
|  | GAS<br><b>R290</b> | <br>40 mm | <b>C</b><br>ENERGY CLASS | <b>3</b><br>CLIMATIC CLASS | <br>38°C |
|  |                    |           |                          |                            |          |

## DETAILS

|   |   |                                    |
|---|---|------------------------------------|
|   |   |                                    |
| Set of 2 drawers as separated kit               | Set of 3 drawers as separated kit       | Foamed door handle                 |
|   |   |                                    |
| Ventilated unit                                 | Stainless steel feet                    | Adjustable chrome shelves          |
|   |   |                                    |
| Adjustable stainless steel shelves anti-tipping | Easily acces for clean condenser filter | Wine shelves available as optional |



## GENERAL FEATURES

- N.4 Hinged SOLID door BACK BAR
- External in black powder coated galvanized steel and white coated steel for internal side
- Item with mat finishing and total height at 860mm
- Ventilated Cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (40mm per side)
- Digital thermostat with membrane
- Door: Self closing and reversible door fitted as standard
- Removable Gasket and door lock fitted as standard
- Motor fan with low noise level performance
- Adjustable shelves: 4 Pcs
- Removable bottom shelf as standard
- Drawer cassette system as optional
- Anticondesantion profile system
- Easily acces for clean condenser filter
- N.4 Adjustable feet - S/S feet or castor with brake (Option)
- Energy efficiency class: C

## TECHNICAL SPECIFICATIONS

|                                  |                      |
|----------------------------------|----------------------|
| Capacity                         | <b>618 L</b>         |
| Temperature                      | <b>+2° ~ +8°C</b>    |
| Consumption                      | <b>3.96 kWh/24h</b>  |
| Rated Power                      | <b>385 W</b>         |
| Noise level                      | <b>53 dB(A)</b>      |
| Net Weight                       | <b>149 Kg</b>        |
| Gross Weight                     | <b>182 Kg</b>        |
| External Dimensions (WxDxH mm)   | <b>2540x515x860</b>  |
| Internal Dimensions (WxDxH mm)   | <b>2160x415x740</b>  |
| Packaging dimensions (WxDxH mm)  | <b>2590x590x1045</b> |
| Loading quantities 20'/40'/40'HQ | <b>12/24/24</b>      |

## CERTIFICATION



## PRODUCT DIMENSIONS

